




PRODUCTS SPECIFICATIONS

Power Supply

<p>PSPI-12V15W (Plug-In)</p> <ul style="list-style-type: none"> ▪ Power Input: 120/240VAC ▪ Power Output: 12VDC – 15W ▪ Protection: Hiccup with auto recovery to 1.1 to 1.3 I_o ▪ Temperature Range: (32°F to 104°F) 0°C to 40°C ▪ Application: Indoor. Outdoor: needs to be housed in a weather proof cover ▪ Approval: UL, CE 	 <p>A small, black, rectangular plug-in power supply with a two-prong AC cord and a DC output terminal.</p>
<p>PSWI-12V20W (Wire-In)</p> <ul style="list-style-type: none"> ▪ Power Input: 120/240VAC ▪ Power Output: 12VDC – 20W ▪ Protection: Over-voltage, Over current and Short circuit protection: Auto-recovery ▪ Temperature Range: (-22°F to 140°F) -30°C to 60°C ▪ Application: Indoor and Outdoor, Suitable for damp location ▪ Approval: UL, CE 	 <p>A small, beige, rectangular wire-in power supply with two AC input wires and two DC output wires.</p>
<p>PSWI-12V40W (Wire-In)</p> <ul style="list-style-type: none"> ▪ Power Input: 120/240VAC ▪ Power Output: 12VDC – 40W ▪ Protection: Over-voltage, Over current and Short circuit protection: Auto-recovery ▪ Temperature Range: (-22°F to 140°F) -30°C to 60°C ▪ Application: Indoor and Outdoor, Suitable for damp location ▪ Approval: UL, CE 	 <p>A larger, beige, rectangular wire-in power supply with two AC input wires and two DC output wires. The label includes technical specifications and safety markings.</p>